



**Recommended
PCB HOLE**

ELECTRICAL PERFORMANCE:

1. Impedance : 50 ohms
2. Frequency Range : 0~6 GHz
3. Working Voltage : 170 Vrms maximum
4. Dielectric Withstanding Voltage : 500 Vrms minimum
5. Insulator Resistance : 1000 Megohms minimum

DESCRIPTION	MATERIALS	FINISHED
LOCK WASHER	BRASS	GOLD/NICKEL
CONTACT	BRASS	GOLD 30u"
INSULATOR	TEFLON	NONE
BODY	BRASS	GOLD/NICKEL
INSULATOR	TEFLON	NONE
BODY	BRASS	GOLD/NICKEL

ORDER	FINISHED
M102-000A	GOLD
M102-001A	NICKEL

REV.	DESCRIPTION	ECN	DRAWN	DATE
C	SEE ECN	00-099	TINA	04-06'2000
B	SEE ECN	00-013	ARVIN	1/18'2000
1	CHANGE ELECTRICAL RATING	98-196	JEFF	7/17/98"
A	NEW RELEASE	98-126	JEFF	5/20/98"

REVISIONS

REMARKS:	TITLE: MMCX R/A JACK PCB RECEPTACLE	
	DESIGNED: JEFF 98.05.20	DRAWN: JEFF 98.05.20
	CHCKED:	APPROVAL:
	TOLERANCES: DIM. XX=±0.3 UNIT: mm XXX=±0.15	

INPUT OUTPUT

P/No.: S-M102-00*A

SHEET: 1 OF 1	SCALE: 20:1
DWG NO.: S-M100	
LAYER: ASY	REV.: C