



Recommended Cable Stripping Dim's

**ELECTRICAL PERFORMANCE:**

- 1.Impedance : 50 ohms
- 2.Frequency Range : 0~6 GHz
- 3.Working Voltage : 170 Vrms maximum
- 4.Dielectric Withstanding Voltage : 500 Vrms minimum
- 5.Insulator Resistance : 500 Megohms minimum

ITEM	DESCRIPTION	MATERIALS	FINISHED	PART NUMBER
3	FERRULE	BRASS	GOLD	14A001-104
2	BODY CAP	BRASS	GOLD	10M000-104
1	CONTACT	BE.COPPER	GOLD 30u"	M701-300A1
	INSULATOR	TEFLON	NONE	
	BODY (2)	BRASS	GOLD	
	BODY (1)	BRASS	GOLD	

REV.	DESCRIPTION	ECN	DRAWN	DATE
B	SEE ECN	02-222	LUKE	07/10/2002
A	NEW RELEASE(M910702)	02-209	LUKE	07/02/2002
1	SAMPLE RELEASE	S-01141	ANGELA	08/25'2001

REVISIONS

REMARKS:		TITLE: MMCX R/A JACK,CRIMP TYPE FOR RG174,188,316/U CABLE	
DESIGNED: ANGELA 08/25'2001	DRAWN: ANGELA 08/25'2001	SHEET: 1 OF 1	SCALE: 8:1
CHECKED:	APPROVAL:	DWG NO.: M701-300A	LAYER: ASY
TOLERANCES: DIM. XX=±0.3 UNIT: mm XX=±0.15		REV. B	P/No: S-M701-300A

**INPUT OUTPUT**