


ELECTRICAL RATINGS:

- 1.Impedance : 50 ohms
- 2.Frequency Range : 0~4GHz
- 3.Working Voltage : 500 Vrms maximum
- 4.Dielectric Withstanding Voltage : 1000 Vrms maximum
- 5.Insulator Resistance : 5000 Megohms minimum

A107-911A	NICKEL	0.8
A107-901A	NICKEL	1.6
A107-910A	GOLD	0.8
A107-900A	GOLD	1.6
PART NUMBER	FINISHED	DIM "A"

INSULATOR	TEFLON	NONE
CONTACT	BERYLLIUM COPPER	GOLD 30U"
BODY	BRASS	GOLD/NICKEL
DESCRIPTION	MATERIALS	FINISHED

D	SEE ECN	01-240	TINA	08-10'2001	MATERIAL:	TITLE: SMA STRAIGHT JACK EDGE MOUNT RECEPTACLE			 INPUT OUTPUT	
C	SEE ECN	01-152	CATHY	05-22'2001						
B	SEE ECN	01-144	TINA	05-08'2001	FINISHED:	DESIGNED: DANNY 03/07'2000	DRAWN: DANNY 03/07'2000	SHEET: 1 OF 1		SCALE: 15:1
E	SEE ECN (M920313)	03-106	Amour	3-7'2003	TOLERANCES: DIM. XX=±0.1 UNIT: mm XXX=±0.05	CHECKED:	APPROVAL:	DWG NO.: A107		
REV.	DESCRIPTION	ECN	DRAWN	DATE	LAYER: SALE		REV. E	P/No.: A107-9**A		
REVISIONS										