



Recommended panel hole

D.C.C.
2004/05/17
Control Copy

DESCRIPTION	MATERIALS	FINISHED
CONTACT	BERYLLIUM COPPER	GOLD 30U"
INSULATOR	TEFLON	NONE
BODY	BRASS	GOLD/NICKEL

ORDER	FINISHED
A503-900A	GOLD
A503-901A	NICKEL

ELECTRICAL PERFORMANCE:

1. Impedance : 50 ohms
2. Frequency Range : 0 ~12.4 GHz
3. Working Voltage : 335 Vrms maximum
4. Dielectric Withstanding Voltage : 1000 Vrms maximum
5. Insulator Resistance : 1000 Megohms minimum

REV.	DESCRIPTION	ECN	DRAWN	DATE
D	SEE ECN(3106-0002)	03-482	Sammi	11-28'2003
C	SEE ECN	00-291	TINA	08-17'2000
B	SEE ECN	00-099	TINA	04-05'2000
E	SEE ECN(3106-0032)	04-191	Sammi	05-13'2004

REVISIONS

REMARKS:

TOLERANCES:
DIM. XX=±0.3
UNIT: mm XXX=±0.15

TITLE: SMA STRAIGHT JACK PANEL RECEPTACLE WITH 2-HOLE AND SOLDER POT TERMINAL

DESIGNED: TINA 02-11'2000	DRAWN: TINA 02-11'2000	SHEET: 1 OF 1	SCALE: 4:1
CHECKED:	APPROVAL:	DWG NO.: S-A503-90*A	

INPUT OUTPUT

P/No.: A503-90*A