



RECOMMENDED
PANEL HOLE

ORDER	FINISHED
A304-900A	GOLD
A304-901A	NICKEL

ELECTRICAL PERFORMANCE:

1. Impedance : 50 ohms
2. Frequency Range : 0~12.4 GHz
3. Working Voltage : 335 Vrms maximum
4. Dielectric Withstanding Voltage : 1000 Vrms maximum
5. Insulator Resistance : 1000 Megohms minimum

3	NUT	BRASS	GOLD/ NICKEL
2	WASHER	BRASS	GOLD/ NICKEL
1	INSULATOR	TEFLON	NONE
	CONTACT	BE. COPPER	GOLD 30U"
	BODY	BRASS	GOLD/ NICKEL
ITEM	DESCRIPTION	MATERIALS	FINISHED

REV.	DESCRIPTION	ECN	DRAWN	DATE	TOLERANCES: DIM. XX=±0.3 UNIT: mm XXX=±0.15	CHECKED:	APPROVAL:	SHEET: 1 OF 1	SCALE: 5:1	
B	SEE ECN	00-099	TINA	04-05'2000	REMARKS:	TINA 02-29'2000	TINA 02-29'2000	S- A304	REV. B	
A	NEW RELEASE	00-056	TINA	03-13'2000						
REVISIONS					TITLE: SMA BULKHEAD RECEPTACLE JACK					