



Recommended
PCB Hole

ELECTRICAL PERFORMANCE:

- 1.Impedance : 50 ohms
- 2.Frequency Range : 0~4 GHz
- 3.Working Voltage : 335 Vrms maximum
- 4.Dielectric Withstanding Voltage : 1000 Vrms maximum
- 5.Insulator Resistance : 1000 Megohms minimum

ORDER	FINISHED
B101-900A	GOLD
B101-901A	NICKEL

INSULATOR	TEFLON	NONE
CONTACT	BRASS	GOLD 30u"
BODY	BRASS	GOLD/NICKEL
DESCRIPTION	MATERIALS	FINISHED

REV.	DESCRIPTION	ECN	DRAWN	DATE	REMARKS:	TOLERANCES: DIM. XX=±0.3 UNIT: mm XX=±0.15	TITLE: SMB STRAIGHT JACK PCB RECEPTACLE	DESIGNED: TINA 02-11'2000	DRAWN: TINA 02-11'2000	CHECKED:	APPROVAL:	SHEET: 1 OF 1	SCALE: 5:1	DWG NO.: S-B101	LAYER: ASY	REV. B	P/No.: S - B101-90*A
B	SEE ECN	00-099	TINA	04-05'2000													
A	NEW RELEASE	00-036	TINA	02-11'2000													
REVISIONS																	



INPUT OUTPUT
INDUSTRIAL CO., LTD.