







D-SUB SERIES

D-sub Series Specifications

D-sub Series

Description	Field Installable, 180° Male Connector with Male Pin	Molded with Cable, 180° Male Connector with Male Pin	Front Panel Mount with Female Pin
Figure			

Drawing			
----------------	---	--	---







Part-No.	Contacts	Cable Range(mm)	Part Number	Contacts	Cable Range(mm)	Part Number	Contacts	Part Number
		9(5A)	4.5-6.5	31009211-01	9(5A)	4.5-8.0	31009213-01-XXX	9(5A)
	15(2A)	4.5-6.5	31015211-01	15(2A)	4.5-8.0	31015213-01-XXX	15(2A)	31015516-01

Specifications			
Number of Contacts	9		15
Wire Gauge	0.3mm ² (22AWG)		0.2mm ² (24AWG)
Cable Range/Panel Thickness	4.5mm - 6.5mm	4.5mm - 8.0mm	Max. 2.0mm
Environmental Protection	IP67		
Mechanical Life	500 mating cycles		
Operating Temperature	- 45°C - 105°C		
Voltage Rating	90V		90V
Rated Current (40°C)	5A		2A

D-SUB SERIES

D-sub Series Specifications

D-sub Series

Description	Field Installable, 180° Male Connector with Female Pin	Molded with Cable, 180° Male Connector with Female Pin	Front Panel Mount with Male Pin																								
Figure																											
Drawing																											
Part-No.	<table border="1"> <thead> <tr> <th>Contacts</th> <th>Cable Range(mm)</th> <th>Part Number</th> </tr> </thead> <tbody> <tr> <td>9(5A)</td> <td>4.5 - 6.5</td> <td>31009111-01</td> </tr> <tr> <td>15(2A)</td> <td>4.5 - 6.5</td> <td>31015111-01</td> </tr> </tbody> </table>	Contacts	Cable Range(mm)	Part Number	9(5A)	4.5 - 6.5	31009111-01	15(2A)	4.5 - 6.5	31015111-01	<table border="1"> <thead> <tr> <th>Contacts</th> <th>Cable Range(mm)</th> <th>Part Number</th> </tr> </thead> <tbody> <tr> <td>9(5A)</td> <td>4.5 - 8.0</td> <td>31009113-01-XXX</td> </tr> <tr> <td>15(2A)</td> <td>4.5 - 8.0</td> <td>31015113-01-XXX</td> </tr> </tbody> </table>	Contacts	Cable Range(mm)	Part Number	9(5A)	4.5 - 8.0	31009113-01-XXX	15(2A)	4.5 - 8.0	31015113-01-XXX	<table border="1"> <thead> <tr> <th>Contacts</th> <th>Part Number</th> </tr> </thead> <tbody> <tr> <td>9(5A)</td> <td>31009616-01</td> </tr> <tr> <td>15(2A)</td> <td>31015616-01</td> </tr> </tbody> </table>	Contacts	Part Number	9(5A)	31009616-01	15(2A)	31015616-01
	Contacts	Cable Range(mm)	Part Number																								
9(5A)	4.5 - 6.5	31009111-01																									
15(2A)	4.5 - 6.5	31015111-01																									
Contacts	Cable Range(mm)	Part Number																									
9(5A)	4.5 - 8.0	31009113-01-XXX																									
15(2A)	4.5 - 8.0	31015113-01-XXX																									
Contacts	Part Number																										
9(5A)	31009616-01																										
15(2A)	31015616-01																										

Specifications

Number of Contacts	9	15
Wire Gauge	0.3mm ² (22AWG)	0.2mm ² (24AWG)
Cable Range/Panel Thickness	4.5mm - 6.5mm	4.5mm - 8.0mm Max. 2.0mm
Environmental Protection	IP67	
Mechanical Life	500 mating cycles	
Operating Temperature	- 45°C - 105°C	
Voltage Rating	90V	90V
Rated Current (40°C)	5A	2A