


**NOTE:**

1. NOMINAL IMPEDANCE 50 OHMS.
2. FREQUENCY RANGE: 0 ~ 4 GHz.
3. WORKING VOLTAGE: 500 V.
4. INSULATION RESTASTANCE: 5000 MEGOHMS MIN.
5. DIELECTRIC WITHSTANDING VOLTAGE: 1500 VOLTS RMS.

CONTACT	P.BRONZE	GOLD 6u"
INSULATOR	P.P	NONE
BODY	ZINC ALLOY	TIN
<b>DESCRIPTION</b>	<b>MATERIAL</b>	<b>PLATING</b>

					REMARKS:	TITLE: BNC MINI R/A JACK PCB RECEPTACLE			 <b>INPUT OUTPUT</b>	
C	SEE ECN	00-152	TINA	05-17'2000		DESIGNED: <b>RICKY</b> 03-10'98	DRAWN: <b>RICKY</b> 03-10'98	SHEET: 1 OF 1		SCALE: 2.5:1
B	SEE ECN	99-025	ANGELA	01-22'99		DWG NO.: <b>S-3139</b>				
A	NEW RELEASE	98-044	RICKY	03-10'98		CHECKED:	APPROVAL:	LAYER: <b>ASY</b>		REV. <b>C</b>
REV.	DESCRIPTION	ECN	DRAWN	DATE	TOLERANCES: DIM. XX=±0.3 UNIT: mm   X.XX=±0.15				P/No.: <b>S-3139-100A</b>	
<b>REVISIONS</b>										