


Recommended Panel Hole

NOTES:

1. NOMINAL IMPEDANCE: 50 OHMS.
2. FREQUENCY RANGE: 0-4 GHz.
3. MAX PEAK VOLTAGE: 500 V.
4. INSULATION RESISTANCE: 5000 MEGOHMS MIN.
5. DIELECTRIC WITHSTANDING VOLTAGE: 1500 VOLTS RMS.

ITEM	DESCRIPTION	MATERIAL	FINISHED	PART NUMBER	Q'TY
4	GND LUG	SK-5	TIN	053003-508	1
3	LOCK WASHER	SK-5	NICKEL	083001-509	1
2	NUT	IRON	NICKEL	073006-609	1
1	CONTACT	P. BRONZE	GOLD	3324-001A1	1
	INSULATOR	DELRIN	NONE		
	BODY	ZINC ALLOY	NICKEL		

REV.	DESCRIPTION	ECN	DRAWN	DATE	TOLERANCES: DIM. XX=±0.3 UNIT: mm XXX=±0.15	CHECKED:	APPROVAL:	TITLE: BNC STRAIGHT JACK BULKHEAD RECEPTACLE	DESIGNED:	DRAWN: ALLEN 98.03.03	SHEET: 1 OF 1	SCALE: 2:1	DWG NO.: 3324-001A	LAYER: ASY	REV. E	P/No.: S-3324-001A
E	SEE ECN	01-388	TINA	12-28'2001	REMARKS:											
D	SEE ECN	98-412	ANGELA	98.12.23												
C	CHANGE DIMENSION	98-033	ALLEN	98.03.03												
REVISIONS																