



**ELECTRICAL PERFORMANCE:**

1. IMPEDANCE : 50 Ohms
2. FREQUENCY : 0~6.0 GHz
3. WORKING VOLTAGE : 335 Vrms MAXIMUM
4. DIELECTRIC WITHSTANDING VOLTAGE : 1000 Vrms MAXIMUM
5. INSULATOR RESISTANCE : 5000 MEGOhms



CONTACT	BE. COPPER	COLD 30u"
INSULATOR	TEFLON	NONE
BODY	BRASS	GOLD
<b>DESCRIPTION</b>	<b>MATERIALS</b>	<b>FINISHED</b>

REV.	DESCRIPTION	ECN	DRAWN	DATE
C	ADD DIM. CO.1 & Ø3.50	01-268	TINA	09-03' 2001
B	ADD DIM. Ø0.95±0.05 & Ø3.10	01-261	TINA	8-28' 2001
A	NEW RELEASE	01-219	ARVIN	7/24' 2001

REVISIONS

REMARKS:	TITLE: MCX STRAIGHT JACK EDGE CARD PCB RECEPTACLE		 <b>INPUT OUTPUT</b>
TOLERANCES: DIM. X. X=±0.3 UNIT: mm X.XX=±0.15	DESIGNED: ARVIN 7/24' 2001	DRAWN: ARVIN 7/24' 2001	
	SHEET: 1 OF 1      SCALE: 10=1		
	DWG NO.: X111-010A		
CHECKED:	APPROVAL:	LAYER: ASY      REV. C	P/No. 'S-X111-010A