



Recommended Cable Detail

ORDER	FINISH
B703-003B	GOLD
B703-004B	NICKEL

ELECTRICAL RATINGS:

- 1.Impedance : 75 ohms
- 2.Frequency Range : 0~4 GHz
- 3.Working Voltage : 335 Vrms maximum
- 4.Dielectric Withstanding Voltage : 1000 Vrms maximum
- 5.Insulator Resistance : 1000 Megohms minimum
- 6.VSWR : 1.25+0.04f(GHz)

ITEM	DESCRIPTION	MATERIALS	FINISHED	PART NUMBER
4	HEAT SHRINK TUBE	PE	NONE	22A000-001
3	FERRULE	BRASS	GOLD/NICKEL	14A000-104/14A000-109
2	BODY CAP	BRASS	GOLD/NICKEL	10A000-104/10A000-109
1	BODY	BRASS	GOLD/NICKEL	B703-00*B
	CONTACT	BE.COPPER	GOLD	
	INSULATOR	TEFLON	NONE	
	SHELL	BRASS	GOLD/NICKEL	
	OUTER CONTACT	P.BRONZE	GOLD/NICKEL	

REV.	DESCRIPTION	ECN	DRAWN	DATE
B	SEE ECN(G920107)	03-047	Amour	2-7'2003
A	NEW RELEASE	98-114	Whaiki Ma	04.24.'98

REVISIONS

REMARKS:

TOLERANCES:
DIM. X.X=±0.3
UNIT: mm X.XX=±0.15

TITLE: 75 Ohms SMB R/A PLUG CRIMP TYPE FOR RG179/U CABLE

DESIGNED: JEFF 01.12.'98
DRAWN: JEFF 01.12.'98
SHEET: 1 OF 1
SCALE: 5:1
DWG NO.: B703B
LAYER: SALE
CHECKED: APPROVAL:

INPUT OUTPUT
INDUSTRIAL CO., LTD.

P/No.: S - B703-00*B