


Recommended Cable Stripping Dim's

ELECTRICAL RATINGS:

1. Impedance : 50 ohms
2. Frequency Range : 0~3 GHz
3. Working Voltage : 250 Vrms maximum
4. Dielectric Withstanding Voltage : 750 Vrms maximum
5. Insulator Resistance : 1000 Megohms minimum

Recommended panel hole



4	FERRULE	BRASS	NICKLE
3	BUSHING	TEFLON	NONE
2	CONTACT	BRASS	GOLD
1	WASHER	BRASS	NICKLE
	INSULATOR	DELTRIN	NONE
	GASKET	RUBBER	NONE
	WASHER	STEEL	NICKLE
	NUT	BRASS	NICKLE
	BODY (2)	BRASS	NICKLE
	BODY (1)	BRASS	NICKLE
ITEM	DESCRIPTION	MATERIALS	FINISHED

REV.	DESCRIPTION	ECN	DRAWN	DATE
D	SEE ECN (M910618)	02-198	Amour	06-24'2002
C	SEE ECN	01-374	LUKE	11/19/2001
F	SEE ECN (3107-0268)	04-190	Sammi	05-13'2004
E	SEE ECN (M911020)	02-395	Amour	10-15'2002
REVISIONS				

REMARKS:

TOLERANCES:
DIM. XX=±0.3
UNIT: mm XXX=±0.15

TITLE: TNC FEMALE BULKHEAD JACK, CRIMP TYPE FOR RG174/U CABLE

DESIGNED: Dick 11-17'99
DRAWN: Dick 11-17'99

CHECKED: APPROVAL:

SHEET: 1 OF 1
SCALE: 3:1

DWG NO.: S-4710-W02A

INPUT OUTPUT

P/No.: 4710-W02A