



ORDER	FINISHED
A820-000A	GOLD
A820-001A	NICKEL

ELECTRICAL RATINGS:

1. Impedance : 50 ohms
2. Frequency Range : 0~3GHz
3. Working Voltage : 170 Vrms maximum
4. Dielectric Withstanding Voltage : 500 Vrms maximum
5. Insulator Resistance : 500 Megohms minimum

CONTACT	BRASS	GOLD 30u"
SHELL	BRASS	NICKEL/GOLD
GASKET	SI. RUBBER	NONE
"C" RING	STEL	NONE
INSULATOR	TEFLON	NONE
BODY	BRASS	NICKEL/GOLD
DESCRIPTION	MATERIALS	FINISHED

					REMARKS.	TITLE: SMA PLUG TO Hirose ADAPTER					
						DESIGNED: LUKE 01/27/2003	DRAWN: LUKE 01/27/2003	SHEET: 1 OF 1	SCALE: 8:1		
REV.	DESCRIPTION	ECN	DRAWN	DATE	TOLERANCES. DIM. XX-±0.3 UNIT: mm XX-±0.16	CHECKED:	APPROVAL:	DWG NO.: A820-	LAYER: ASY	REV. A	P/No : S-A820-00*A
REVISIONS											